

HANDZENDERS



12200940332 - Sesam 800 Keyring

- Number of functions/buttons: 3
- Temperature range: -25 to +55°C
- Radio frequency: 869.8 MHz
- Output power: 5 mW
- Battery: CR2025 X2, 6V (2x3V)
- Power consumption: 15 mA during transmission
- Protection class: IP65
- Dimensions: 67 x 44 x 13 mm
- Weight: 30 g



12200940332 - Sesam 800 - Small 3

- Number of functions/buttons: 3
- Temperature range: -25 to +55°C
- Radio frequency: 869.8 MHz
- Output power: 5 mW
- Battery: 3V (2x AAA)
- Power consumption: 15 mA during transmission
- Protection class: IP67
- Dimensions: 75 x 46 x 22 mm
- Weight: 80 g



12200944574 - Sesam 800 - Small 6

- Number of functions/buttons: 6
- Temperature range: -25 to +55°C
- Radio frequency: 869.8 MHz
- Output power: 5 mW
- Battery: 3V (2x AAA)
- Power consumption: 15 mA during transmission
- Protection class: IP67
- Dimensions: 75 x 46 x 22 mm
- Weight: 80 g



12200940338 - Sesam 800 - Medium 6

- Number of functions/buttons: 6
- Temperature range: -25 to +55°C
- Radio frequency: 869.8 MHz
- Output power: 5 mW
- Battery: 3V (2x AA)
- Power consumption: 15 mA during transmission
- Protection class: IP67
- Dimensions: 100 x 60 x 25 mm
- Weight: 130 g



12200940340 - Sesam 800 - Large 15

- Number of functions/buttons: 15
- Temperature range: -25 to +55°C
- Radio frequency: 869.8 MHz
- Output power: 5 mW
- Battery: 3V (2x AA)
- Power consumption: 15 mA during transmission
- Protection class: IP67
- Dimensions: 120 x 75 x 30 mm
- Weight: 200 g



12200940341 - Sesam 800 - Large 99

- Number of functions/buttons: 3
- Temperature range: -25 to +55°C
- Radio frequency: 869.8 MHz
- Output power: 5 mW
- Battery: 3V (2x AA)
- Power consumption: 15 mA during transmission
- Protection class: IP67
- Dimensions: 120 x 75 x 30 mm
- Weight: 200 g

ONTVANGERS



12200942216 - Sesam 800 - DIN - RX12/24V - Ontvanger

- No. of outputs: 1 or 3
- Radio frequency: 869.8 MHz
- Power consumption: 60mA (+30mA when the relay is active at 12V DC)
- Temperature range: -25 to +70°C
- Dimensions: 85 x 75 x 30 mm
- Weight: 180 g
- Supply voltage: 12-24V AC/DC



12200941244 - Sesam 800 - RX 12-24V - Ontvanger

- No. of outputs: 1 or 3
- Radio frequency: 869.8 MHz
- Power consumption: 60mA
- Temperature range: -25 to +70°C
- Dimensions: 120 x 90 x 51 mm
- Weight: 450 g
- Supply voltage: 12-24V AC/DC



12200940156 - Sesam 800 - RX 230V - Ontvanger

- No. of outputs: 1 or 3
- Radio frequency: 869.8 MHz
- Power consumption: 60mA
- Temperature range: -25 to +70°C
- Dimensions: 120 x 90 x 51 mm
- Weight: 450 g
- Supply voltage: 230 V AC



12200941243 - Sesam 800 - RXD 12-24V - Ontvanger

- No. of outputs: 1 or 3
- Radio frequency: 869.8 MHz
- Power consumption: 60mA
- Temperature range: -25 to +70°C
- Dimensions: 120 x 90 x 51 mm
- Weight: 450 g
- Supply voltage: 12-24V AC/DC



12200940224 - Sesam 800 - RXD 230V - Ontvanger

- No. of outputs: 1 or 3
- Radio frequency: 869.8 MHz
- Power consumption: 60mA
- Temperature range: -25 to +70°C
- Dimensions: 120 x 90 x 51 mm
- Weight: 450 g
- Supply voltage: 230 V AC